



- ① SIDE LOT EASEMENTS WILL REQUIRE THE SAME DIMENSIONS AND SPACE ALLOCATION AS EASEMENT ON REAR LOT LINE WHETHER IT BE CENTERED ON, ADJACENT TO, SIDE LOT LINE.
- ② CUSTOMER'S SERVICE LATERALS MUST HAVE A MINIMUM OF 24" EARTH COVER AND MUST CLEAR ALL OTHER UTILITIES BY 4" OR MORE. PER NESC 352D

- ③ IN TYPICAL EAST-WEST AND NORTH-SOUTH EASEMENTS, THE ARRANGEMENT WILL BE GENERALLY AS SHOWN. IN CURVILINEAR DEVELOPMENT PATTERNS, STANDARD ALLOCATED LOCATIONS IN REFERENCE TO THE NORTH AND EAST SIDE WILL BE AT A CONVENIENT STARTING PLACE AND WILL USUALLY BE DECIDED BY MUTUAL AGREEMENT. CROSSOVERS WILL NOT BE MADE ALONG THE EASEMENT.
- ④ THE SECONDARY PEDESTAL SHOULD BE INSTALLED 90 DEGREES TO THE TRENCH.

DRAWN 1-6-98		H. BOWLDEN		SECTION 31	SUB-SECTION 420
CHECKED 1-7-98		JAMES C. DAVIS		SHEET 1 OF 1 SHEETS	
APPROVED 1-7-98		R.K. MURPHY		DRAWING NUMBER	
				004	269 03

2	08-27-18	REVISED NOTE 2	SCM	JCD	TRS
1	11-24-03	REVISED PLACEMENT OF SECONDARY PEDESTAL & ADDED NOTE 4	LRM	JCD	LHH
NO.	DATE	REVISION	BY	CH	APP.